

iBend A Series	Bending Power Force	Bending length	Distance Between Columns	Stroke	Daylight	Throat	Table Height	Table Height Below Ground	Backgauge Speed			Backgauge Stroke	Length	Height	Width	Crowning		Rapid Approach Speed	Pressing Speed	Return Speed	Hydraulic tank	Main motor	Weight
	ton.	A	B	C	J	D	E	F	X Axis	X-R Axis		X Axis	G	H	L	Manual	Motorized	mm/sec	mm/sec	mm/sec	Lt	Kw.	kg
		mm.	mm.	mm.	mm.	mm.	mm.	mm.	mm.	X Axis Speed	X Axis Speed	R Axis Speed	mm.	mm.	mm.								
										(mm/s)	(mm/s)	(mm/s)											
A40-1250	40	1250	1100	260	465	400	870	xx	100	500	300	500	2750	2400	1950	-	-	120	9	100	95	4	3050
A60-2100	60	2100	1600	260	465	400	880	xx	100	500	300	500	3600	2400	2100	-	-	120	10	120	110	4	4850
A60-2600	60	2600	2150	260	465	400	880	xx	100	500	300	500	4150	2400	2150	Optional	Optional	120	10	120	110	5,5	5300
A100-2600	100	2600	2150	260	465	400	880	xx	100	500	300	500	4150	2430	2150	Optional	Optional	120	10	120	110	7,5	5800
A100-3100	100	3100	2600	260	465	400	900	xx	100	500	300	500	4750	2450	2200	Optional	Optional	120	10	120	180	7,5	6450
A135-3100	135	3100	2600	260	465	400	920	xx	100	500	300	500	4750	2500	2500	Optional	Optional	120	10	120	180	11	7600
A175-3100	175	3100	2600	260	465	400	920	xx	100	500	300	500	4750	2600	2675	Optional	Optional	120	10	120	180	15	8800
A220-3100	220	3100	2600	260	465	400	930	xx	100	500	300	500	4800	2730	2700	Optional	Optional	110	10	120	290	18,5	10800
A270-3100	270	3100	2600	260	465	400	950	xx	100	500	300	500	4850	2850	2800	Optional	Optional	100	10	120	290	22	13100
A320-3100	320	3100	2600	260	465	400	970	xx	100	500	300	500	4850	2900	2850	Optional	Optional	100	9	120	290	22	14200
A135-3700	135	3700	3200	260	465	400	930	xx	100	500	300	500	5450	2600	2500	Optional	Optional	120	10	120	180	11	8600
A175-3700	175	3700	3200	260	465	400	940	xx	100	500	300	500	5450	2800	2675	Optional	Optional	120	10	120	180	15	9900
A220-3700	220	3700	3200	260	465	400	940	xx	100	500	300	500	5450	2900	2700	Optional	Optional	110	10	120	290	18,5	12000
A320-3700	320	3700	3200	260	465	400	970	xx	100	500	300	500	5450	3000	2900	Optional	Optional	100	9	120	290	22	15100
A135-4100	135	4100	3200	260	465	400	930	xx	100	500	300	500	5850	2600	2500	Optional	Optional	120	10	120	180	11	9600
A175-4100	175	4100	3200	260	465	400	940	xx	100	500	300	500	5850	2800	2675	Optional	Optional	120	10	120	180	15	11000
A220-4100	220	4100	3200	260	465	400	940	xx	100	500	300	500	5850	2900	2700	Optional	Optional	110	10	120	290	18,5	12900
A270-4100	270	4100	3200	260	465	400	950	xx	100	500	300	500	5850	3000	2800	Optional	Optional	100	10	120	290	22	14700
A320-4100	320	4100	3200	260	465	400	970	xx	100	500	300	500	5850	3050	2850	Optional	Optional	100	9	120	290	22	16300
A400-4100	400	4100	3200	310	550	500	1250	xx	100	500	300	500	5850	3100	3050	-	Optional	90	8,5	90	370	30	20800
A500-4100	500	4100	3200	310	550	500	850	685	100	500	300	500	5850	3150	3050	-	Optional	80	10	80	550	45	26100
A220-4300	220	4300	3700	260	465	400	950	XX	100	500	300	500	6000	3000	2750	Optional	Optional	110	10	120	290	18,5	14100
A270-4300	270	4300	3700	260	465	400	950	XX	100	500	300	500	6000	3050	2850	Optional	Optional	100	10	120	290	22	15600
A320-4300	320	4300	3700	260	465	400	970	XX	100	500	300	500	6000	3150	2900	Optional	Optional	100	9	120	290	22	17200
A220-5100	220	5100	4200	260	465	400	970	XX	100	500	300	500	6900	3100	2800	Optional	Optional	110	10	120	290	18,5	17900
A270-5100	270	5100	4200	260	465	400	970	XX	100	500	300	500	6900	3150	2900	Optional	Optional	110	10	120	290	22	20400
A320-5100	320	5100	4200	260	465	400	1000	XX	100	500	300	500	6900	3200	2950	Optional	Optional	100	9	120	290	22	22800
A400-5100	400	5100	4200	310	550	500	1050	XX	100	500	300	500	6900	3300	3050	-	Optional	90	8,5	90	410	30	26000
A220-6100	220	6100	5100	260	465	400	1050	xx	100	500	300	500	8000	3000	3050	Optional	Optional	110	10	120	400	18,5	24000
A320-6100	320	6100	5100	260	465	400	1100	xx	100	500	300	500	8000	3050	2950	-	Optional	100	9	120	400	22	29000
A400-6100	400	6100	5100	310	550	500	1150	xx	100	500	300	500	8050	3650	3050	-	Optional	90	8,5	90	400	30	34500
A500-6100	500	6100	5100	310	550	500	900	1450	100	500	300	500	8100	3950	3150	-	Optional	80	10	80	550	37	40000
A600-6100	600	6100	5100	360	600	600	900	1500	100	500	300	500	8150	4300	3300	-	Optional	75	9,5	90	550	45	46000
A800-6100	800	6100	5100	410	650	600	900	1550	100	500	300	500	8200	4500	3500	-	Optional	70	8,7	90	640	55	58000
A1000-6100	1000	6100	5100	510	750	600	900	1700	100	500	300	500	8250	4750	3800	-	Optional	65	7,2	90	1000	55	72000

Technical specifications are subject to change without notice.
Special capacity machines can be manufactured upon request.